



Multicast Address Allocation




PIYUSH HARSH

October 10 2007
pharsh@cise.ufl.edu




Different Approaches

- Static Allocation Schemes
- Flat address allocation schemes
 - IRMA (sdr – Mark Hadley and Van Jacobson)
 - IPRMA (Van Jacobson)
- Hierarchical allocation schemes
 - Contiguous Schemes
 - Prefix based allocation schemes
 - Contiguous Cyclic allocation schemes
 - Non Contiguous Schemes



Characteristics of Good Allocation Scheme

- Ability to successfully allocate addresses while minimizing the number of blocks a child domain holds
 - To keep routing table small
- Minimize the number of times child domain changes address
 - To minimize routing flux
- Maintain high level of utilization



Before we proceed ...

- Multicast address allocation makes sense for Ipv4 (because of its limited multicast address space)
- With IPv6 and alternative multicast protocols like SSM, addressing issue will be resolved
- So why do we care about multicast addressing problem??
 - Because of reluctance of sys admins to use SSM
 - SSM allows each IP host, 16 million multicast addresses
 - Resistance of service providers to migrate to IPv6

Static Allocation Schemes

- GLOP
 - Can be used to assign permanent multicast address to long lived session example TV series broadcast
 - GLOP Addresses are in control of ISPs which have been assigned AS numbers by IANA.
 - But there are only 256 addresses per AS
 - Can not scale to large number of sessions



Flat addressing Schemes

- ▶ IRMA – Informed Random Multicast Address Allocation scheme
 - ★ Used by sdr, a MBONE session directory tool
 - ★ Address collision on the order of $O(\sqrt{N})$
 - ★ For collision free performance: requires global knowledge of currently allocated addresses
- ▶ IPRMA – Informed Partitioned Random Multicast Address ...
 - ★ Whole address space partitioned on the lines of popular TTL boundaries
 - ★ Ideal performance achieved with large number of partitions where address collision improved to $O(N)$
 - ★ Results in oversubscribed and under subscribed partitions
 - ★ Collisions could still result because of asymmetric TTL scoping


Hierarchical Allocation Schemes

- **Prefix based schemes**
 - Don't care bits are the trailing bits, ex A8.76.xx.xx
 - Used in MASC proposal
 - May lead to fragmented and unused address chunks
- **Contiguous schemes**
 - Don't care bits can occur anywhere not only at trailing bits
 - Example: A8.xx.xx.76 (don't care bits may wrap around)
 - Has better address aggregation property (Cyclic)
- **Non Contiguous Allocation Schemes**
 - Don't care bits do not have to appear together
 - Example: Ax.87.xx.6x
 - Has the best address space utilization capability in theory


MASC

- Multicast Address Set Claim

- current IETF proposal for hierarchical dynamic multicast address allocation scheme
- Allows for a child domain to claim a subset of address of its parent domain for allocation purposes
- The child domain listen for address collision for some long time
- In case of no collision, it assigns that subset of addresses to MAAS (Multicast Address Allocation Servers) for assignment to individual multicast sessions.
- Allows for address expansion by migration, doubling etc ...
- Address Aggregation could be challenging and complex
- Over time could result in fragmented address space



Non-Contiguous Vs Prefix Based Allocation Scheme



- Simulations based on various load functions for both non-contiguous and prefix based algorithm shows counter-intuitive results
- For large load, prefix based schemes performed better than the other
- Researchers reasoned this observation on how these two algorithms might partition the address space
- Theoretically non-contiguous algorithms should have performed better, but such an allocation algorithm is still not yet known
- RESEARCH TOPIC??????

Our Solution to IPv4 Multicast Address Allocation ...



Topic of next CONS presentation :D

References